



Confirmation of Product Type Approval 10/FEB/2011

Please refer to the "Service Restrictions" shown below to determine if Unit Certification is required for this product.

This is to certify that, pursuant to the Rules of the American Bureau of Shipping (ABS), the manufacturer of the below listed product held a valid Manufacturing Assessment (MA) with expiration date of 06/DEC/2015. The continued validity of the Manufacturing Assessment is dependent on completion of satisfactory audits as required by the ABS Rules.

And; a Product Design Assessment (PDA) valid until 03/NOV/2015 subject to continued compliance with the Rules or standards used in the evaluation of the product.

The above entitle the product to be called Product Type Approved.

The Product Design Assessment is valid for products intended for use on ABS classed vessels, MODUs or facilities which are in existence or under contract for construction on the date of the ABS Rules used to evaluate the Product.

ABS makes no representations regarding Type Approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for this evaluation.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

DUVALCO VALVE (TIANJIN) CO., LTD. Model Name(s): GB/T 12238-2008 Butterfly Valve

Presented to:

DUVALCO VALVE (TIANJIN) CO., LTD.
GUANGMING INDUSTRIAL AREA,
BEI ZHAKOU TOWN, JINNAN DISTRICT
TIANJIN
China

Intended Service:

Marine Piping System except fire-fighting system, shell connection services and lubricating/fuel oil tank valves subjected to a static head of oil

Description:

Wafer/Lug/Double Flange Type Rubber Lined Butterfly Valve

Ratings:

Design Pressure: 1.0 MPa, Design Temperature: < 150 Deg.C,
DN50/65/80/100/125/150/200/250/300/350/400/450/500/600

Service Restrictions:

1. Unit Certification is not required for this product. If the manufacturer or purchaser request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined. 2. Not suitable for using in the fire-fighting system, shell connection services and lubricating/fuel oil tank valves subjected to a static head of oil, unless gasket materials and materials other than metal are to be tested of passing a recognized fire test acceptable to the Bureau. 3. Wafer type valves are not to be used in any connection to a vessel's shell.

Comments:

1. Valves intended for installation on the side shell at or below the deepest load waterline, including those at the sea chests, are to be hydrostatically tested in the presence of the Surveyor, before installation, to a pressure of at least 5bar. 2. The driving mechanism (Item 18 - Gear Box as indicated on drawings) of butterfly valves is out of the approval scope of this certificate.

Notes / Documentation:

Term of Validity:

This Product Design Assessment (PDA) Certificate 10-SQ646382-PDA, dated 04/Nov/2010 remains valid until 03/Nov/2015 or until the Rules or specifications

used in the assessment are revised (whichever occurs first). This PDA is intended for a product to be installed on an ABS classed vessel, MODU or facility which is in existence or under contract for construction on the date of the ABS Rules or specifications used to evaluate the Product. Use of the Product on an ABS classed vessel, MODU or facility which is contracted after the validity date of the ABS Rules and specifications used to evaluate the Product, will require re-evaluation of the PDA. Use of the Product for non ABS classed vessels, MODUs or facilities is to be to an agreement between the manufacturer and intended client.

ABS Rules: 1-1-Appendix 3, 1-1-4/7.7, 4-6-2/5.11, 4-6-2/7.3, 4-6-2/9.13 of SVR 2010
National Standards: GB/T 12238-2008
International Standards:
Government Authority:
EUMED:
Others:

Model Certificate	Model Certificate No	Issue Date	Expiry Date
PDA	10-SQ646382-PDA	04/NOV/2010	03/NOV/2015



ABS Programs

ABS has used due diligence in the preparation of this certificate and it represents the information on the product in the ABS Records as of the date and time the certificate was printed. Type Approval requires Drawing Assessment, Prototype Testing and assessment of the manufacturer's quality assurance and quality control arrangements. Limited circumstances may allow only Prototype Testing to satisfy Type Approval. The approvals of Drawings and Products remain valid as long as the ABS Rule, to which they were assessed, remains valid. ABS cautions manufacturers to review and maintain compliance with all other specifications to which the product may have been assessed. Further, unless it is specifically indicated in the description of the product; Type Approval does not necessarily waive witnessed inspection or survey procedures (where otherwise required) for products to be used in a vessel, MODU or facility intended to be ABS classed or that is presently in class with ABS. Questions regarding the validity of ABS Rules or the need for supplemental testing or inspection of such products should, in all cases, be addressed to ABS.